



INSTALL IT. TRUST IT.

ArmaFinish 99

The elastic paint designed for protection and covering of ArmaFlex

- // Non-dripping paint
- // Permanently elastic
- // Resistant to weathering
- // Good ageing resistance



 **armacell**[®]
ArmaFlex[®]

TECHNICAL DATA - ARMAFINISH 99

Brief description	ArmaFinish 99 is a paint, which remains permanently elastic, it is resistant to weathering and has good ageing resistance.
Material type	Non-dripping paint.
Product colour range	white (RAL 9001) and grey (RAL 7037), Black
Applications	Protection of ArmaFlex insulation materials when installed outdoors and for marking purposes for interior use.
Installation	All ArmaFlex insulation (except HT/ArmaFlex and ArmaFlex products based on Armaprene, see relevant product data sheet) which are installed outdoors can be coated with two complete coats of Armafinish 99. Paint may be applied using a brush or roller. Clean the tools with water.
Remarks	Unprotected ArmaFlex must not be exposed to weathering for more than 3 days, so the paint should be applied as soon as possible. The protective coating should be inspected at regular intervals. After 2 years at the latest, two further coats should be applied.

Property	Value / Assessment	Standard / Test method
Health and environment		
Health aspects	MSDS available on request.	
Other technical features		
Application conditions	Application temperature: + 10 °C to + 30 °C maximum relative humidity: 80%.	
Cure time	Drying time at + 20 °C: approx. 2 hours. It is also necessary to allow this time between coats; the second coating layer must be applied within 7 days.	
Disposal and recycling	Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company. Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. More details see relevant Safety Data Sheet.	
Hazard class	Environmentally hazardous substance as defined by the transport regulations (ADR/RID, IMDG-Code, ICAO-TI/ IATA-DGR).	
Shelf life	12 months	
Storage	Material shall be stored in a tightly closed container in a cool, well-ventilated place. Protect from frost and do not store it below of + 5°C.	
Yield	Normal consumption: 0,55 l/m ² when two coats are applied (corresponds to a dry film thickness of 0,26mm).	

All data and technical information are based on results achieved under the specific conditions defined according to the testing standards referenced. Despite taking every precaution to ensure that said data and technical information are up to date, Armacell does not make any representation or warranty, express or implied, as to the accuracy, content or completeness of said data and technical information. Armacell also does not assume any liability towards any person resulting from the use of said data or technical information. Armacell reserves the right to revoke, modify or amend this document at any moment. It is the customer's responsibility to verify if the product is suitable for the intended application. The responsibility for professional and correct installation and compliance with relevant building regulations lies with the customer. This document does not constitute nor is part of a legal offer to sell or to contract.

At Armacell, your trust means everything to us, so we want to let you know your rights and make it easier for you to understand what information we collect and why we collect it. If you would like to find out about our processing of your data, please visit our Data Protection Policy.

Trademarks followed by © or ™ are trademarks of the Armacell Group. © Armacell, 2023 All rights reserved.

TDS | 032024 | en-GB

ABOUT ARMACELL

As the inventor of flexible foam for equipment insulation and a leading provider of engineered foams, Armacell develops innovative and safe thermal and mechanical solutions that create sustainable value for its customers. Armacell's products significantly contribute to global energy efficiency making a difference around the world every day. With more than 3,300 employees and 25 production plants in 19 countries, the company operates two main businesses, Advanced Insulation and Engineered Foams. Armacell focuses on insulation materials for technical equipment, high-performance foams for acoustic and lightweight applications, recycled PET products, next-generation aerogel technology and passive fire protection systems.



For more information, please visit:
www.armacell.com