





FOR FIRESTOP PIPES UP TO  
MEDIUM DIAMETERS

# ArmaProtect FC1

Firestop collar for fire seals in walls and  
floors

// For sealing of combustible pipes without insulation up  
to 160 mm diameter



INSTALL IT. ENSURE SAFETY.

---

# ArmaProtect™

Passive fire protection (PFP) products and systems are designed to provide fire-safe circumstances in the event of a fire emergency. Often built as part of the building component, PFP measures are not visible to building users and hence often overlooked as a fire protection measure.



## // Fire safety is top priority

The requirements for fire protection are increasing. Regulated by building codes, buildings are sub-divided in fire compartments. In the event of a fire, they keep fire and smoke contained in a limited area for a given amount of time. Fire ratings typically range from 30 to 120 or even up to 240 minutes

ArmaProtect firestop products reliably seal off penetrations in walls, floors or service shafts and keep escape routes free of smoke and toxic gases. This gives occupants valuable time to leave the building and rescue teams unhindered access for evacuation.

## // One-stop-shop solution

Whether flexible walls, rigid wall or rigid floors with cable and pipe penetrations – Armacell offers specifiers and installers compliant solutions for almost all firestop penetrations.

The range includes intumescent firestop wraps, firestop collars, coated firestop boards, intumescent firestop sealants and mortars.


The ArmaProtect portfolio is an ideal addition to ArmaFlex Protect, Armacell's unique firestop solution which combines high fire resistance, condensation control and thermal insulation in a single product.

**SOLUTIONS  
WITH EN TESTING  
(ETA)**

# The firestop portfolio from Armacell

Firestop penetration seals with cables, conduits, combustible and non-combustible pipes for residential, commercial and industrial building.

- ✓ Specifiable, reliable and flexible – **for each firestop application in residential, commercial and industrial buildings**
- ✓ Cost efficient solution – **the ideal choice for specifiers**
- ✓ Easy to install and maintain – **perfectly designed for the need of installers**
- ✓ Easy to inspect – **compliant solutions to fulfill the expectations of firestop inspectors**
- ✓ Firestop solutions for cable, pipe and mixed penetrations – **globally tested with European Technical Assessments and tested UL systems**
- ✓ Full approval range from small to large openings – **covering customer's requirement on the job sites**



**ArmaProtect EXPS**  
Firestop sealant



**ArmaProtect FW2 & FW3**  
Firestop wrap



**ArmaProtect FC1 & FC2**  
Firestop collar



**ArmaProtect CB**  
Coated firestop board  
(includes **ArmaProtect ABLC**  
Firestop coating and  
**ArmaProtect ABLF**  
Firestop filler mastic)



**ArmaProtect CM**  
Firestop mortar



**ArmaProtect CT**  
Firestop cable tube



**ArmaProtect EFC1 & EFC2**  
Endless firestop collar



## TECHNICAL DATA - ARMAPROTECT FC1

Brief description	ArmaProtect FC1 is a solid metal sleeve equipped with several layers of intumescent material to maintain the fire resistance performance of fire penetrations in walls and floors.
Material type	Galvanised sheet steel housing with flexible intumescent strip.
Product colour range	Housing: silver grey Intumescent material: anthracite
Special features	Easy visual inspection.
Product range	50 mm to 160 mm diameter.
Applications	Firestop collar for sealing combustible pipes without insulation.
Installation	For professional use only. Refer to third party published listings, national approvals / assessments and Armacell's product literature for specific application details as well as before handling this product.

### Approvals and compliance

Specification compliance	<ul style="list-style-type: none"> <li>ETA-21/1024 acc. EN 1366-3</li> </ul>
--------------------------	--

Property	Value / Assessment	Standard / Test method
<b>Operating temperature</b>		
Operating temperature	-40°C to 70°C (40°F to 158°F)	
<b>Processing Temperature</b>		
Processing temperature	5°C to 25°C (41°F to 77°F)	
<b>Fire Performance and Approvals</b>		
Reaction to fire	Housing: Class A1 Inlay: Class E	EN 13501-1
Use category	Type Y1: intended for use at temperatures below 0°C with exposure to UV but no exposure to rain	EOTA TR 024
<b>Passive fire protection</b>		
Fire resistance of elements of construction <sup>1</sup>	Drywall, concrete wall, aerated concrete wall, masonry wall: up to EI 120 Concrete floors: up to EI 240	EN 13501-2
<b>Physical attributes</b>		
Thickness	2 mm ± 0,2mm (sheets)	EOTA TR 024
Density	Inlay: 1.02 - 1.42 g/cm <sup>3</sup> (thickness 2 mm)	EOTA TR 024
<b>Mechanical properties</b>		
Expansion pressure	Inlay: > 0.6 N/mm <sup>2</sup>	EOTA TR 024
Weight loss on heating	Inlay: 52 - 62% (at 550°C, 30 minutes)	EOTA TR 024
Expansion ratio	Inlay: 12 - 22.5 times	EOTA TR 024
<b>Health and environment</b>		
Health aspects	Please refer to the safety data sheet available on our website.	
Emission of dangerous substances	No dangerous substances.	
<b>Other technical features</b>		
Storage	Store / Transport in a cool and dry place with an ambient temperature of 5 °C to 25 °C (41°F to 77°F) and protect from frost.	

<sup>1</sup> See ETA 21/1024 for further installation details.

**Firestop collar**

<b>Item</b>	<b>Description</b>	<b>Content [quantity]</b>
PRO-FC1-050	ArmaProtect FC1 Firestop collar Ø 50 mm	50 piece
PRO-FC1-063	ArmaProtect FC1 Firestop collar Ø 63 mm	50 piece
PRO-FC1-075	ArmaProtect FC1 Firestop collar Ø 75 mm	50 piece
PRO-FC1-090	ArmaProtect FC1 Firestop collar Ø 90 mm	40 piece
PRO-FC1-110	ArmaProtect FC1 Firestop collar Ø 110 mm	25 piece
PRO-FC1-125	ArmaProtect FC1 Firestop collar Ø 125 mm	20 piece
PRO-FC1-140	ArmaProtect FC1 Firestop collar Ø 140 mm	16 piece
PRO-FC1-160	ArmaProtect FC1 Firestop collar Ø 160 mm	12 piece

All data and technical information are based on results achieved under the specific conditions defined according to the testing standards referenced. Despite taking every precaution to ensure that said data and technical information are up to date, Armacell does not make any representation or warranty, express or implied, as to the accuracy, content or completeness of said data and technical information. Armacell also does not assume any liability towards any person resulting from the use of said data or technical information. Armacell reserves the right to revoke, modify or amend this document at any moment. It is the customer's responsibility to verify if the product is suitable for the intended application. The responsibility for professional and correct installation and compliance with relevant building regulations lies with the customer. This document does not constitute nor is part of a legal offer to sell or to contract.

At Armacell, your trust means everything to us, so we want to let you know your rights and make it easier for you to understand what information we collect and why we collect it. If you would like to find out about our processing of your data, please visit our Data Protection Policy.

Trademarks followed by © or ™ are trademarks of the Armacell Group. © Armacell, 2023 All rights reserved.

ArmaProtect | ArmaProtect FC1 | Brochure | 062024 | en-VN

## ABOUT ARMACELL

---

As the inventor of flexible foam for equipment insulation and a leading provider of engineered foams, Armacell develops innovative and safe thermal and mechanical solutions that create sustainable value for its customers. Armacell's products significantly contribute to global energy efficiency making a difference around the world every day. With more than 3,300 employees and 25 production plants in 19 countries, the company operates two main businesses, Advanced Insulation and Engineered Foams. Armacell focuses on insulation materials for technical equipment, high-performance foams for acoustic and lightweight applications, recycled PET products, next-generation aerogel technology and passive fire protection systems.

For more information, please visit:  
[www.armacell.com](http://www.armacell.com)

  
MAKING A DIFFERENCE AROUND THE WORLD