

Pipe Insulation (FM Approval Class Number 4924)

Mechanical piping systems such as those used in heating, ventilating, air conditioning, or refrigeration at temperatures not exceeding 220°F (104°C) sometimes need to be insulated for maximum operational efficiency. The insulations listed below have been tested and found to be acceptable in and of themselves, without needing automatic sprinkler protection.

Each insulation should be used with regard for the size and shape limitations, if any, following their respective listings.

Pipe Insulation

Class 0 Armaflex

Class 0 Armaflex thermal insulation, a black flexible, elastomeric thermal insulation product.

Class 0 Armaflex pipe insulation is supplied in wall thicknesses from 9-50 mm (3/8 - 2 in.) on a tubular shape for application over pipes up to a 6 in. (152 mm) dia.

Class 0 Armaflex sheet insulation is supplied in thicknesses from 3-32 mm (1/8-1-1/4 in.) as flat sheet for application over large dia. piping and over ducts. Multiple layers may be installed over large dia. piping up to a max 120 mm (4-3/4 in.) wall thickness.

| | |
|----------------------------|---|
| Company Name: | Armacell GmbH |
| Company Address: | Robert-Bosch-Strasse 10, Munster D-48153, Germany |
| Company Website: | http://www.armacell.com |
| Listing Country: | Germany |
| Certification Type: | FM Approved |