

ArmaPET[®] Insights

TRANSPORT & STORAGE

ArmaPET sheets are stacked on wooden pallets for transport and storage. These pallets comply with the ISPM15 regulation. All pallets are protected in a way that prevents damage at the corners of the material.

Some pallets may be packed with an intermediate pallet in the middle, depending on the material density and thickness. ArmaPET Struct measuring 2448x1008 mm comes on wrapped and protected pallets with a final size of 2455x1035 mm.

The height of the pallet will be adjusted based on the method of transport, and the maximum heights are defined as follows:



ROAD TRANSPORT:

- 2500 mm
- The height will be optimised according to the thickness of the boards.



SEA TRANSPORT:

- 2455 mm for 40 HC containers
- 2100 mm for 20' containers



AIR TRANSPORT:

- 1600 mm for passenger planes
- 2455 mm for cargo planes

The method of shipment cannot be changed after pallets have been packed for a specific order.

DELIVERY & TRANSPORT

Delivery, handling, and transport should be carried out in such a way that the materials are not exposed to moisture or contamination and are protected from damage. Armacell's packaging includes a plastic wrap for protection. It should be ensured that this is not removed before the

material reaches its destination. The material should preferably be stored in its original packaging until it is used. Any impact on pallets must be avoided during transport, stacking, and unloading.

Stacking of full height pallets is not possible for transport.

If claims regarding transport damage are made, a note of the damage must be made on the freight documents and freight invoice. Photographs showing the damage will facilitate the handling of transport claims with the forwarder. Furthermore, the goods must be kept in their original packaging until inspected or released by us.

Delivery & transport conditions according to Incoterms agreed in the contract (FCA/CPT/CIP).

STORAGE

Pallets can be stacked up to two pallets high for storage.

Products must be stored in a dry, normally ventilated area, and protected against any potential risk of contamination or damage. Indoor storage is recommended. We recommend keeping the material in its original packaging until it is used and storing it indoors at not more than 40°C, in a dry atmosphere.

If the material is exposed to temperatures above 40°C, dimensional changes of up to 3% in-plane can be expected, but the mechanical properties will remain unaffected.

SHELF-LIFE

ArmaPET Struct materials have a shelf-life of at least 24 months after production. The product may also be used after the shelf-life period, but Armacell then strongly advises testing or assessment of the material prior to use.

© Armacell, 2021. All rights reserved. ArmaPET® is a trademark of the Armacell Group.

All data and technical information are based on results achieved under the specific conditions defined according to the testing standards referenced. Despite taking every precaution to ensure that said data and technical information are up to date, Armacell does not make any representation or warranty, express or implied, as to the accuracy, content or completeness of said data and technical information. Armacell also does not assume any liability towards any person resulting from the use of said data or technical information. Armacell reserves the right to revoke, modify or amend this document at any moment. It is the customer's responsibility to verify if the product is suitable for the intended application. The responsibility for professional and correct installation and compliance with relevant building regulations lies with the customer. This document does not constitute nor is part of a legal offer to sell or to contract.

At Armacell, your trust means everything to us, so we want to let you know your rights and make it easier for you to understand what information we collect and why we collect it. If you would like to find out about our processing of your data, please visit our Data Protection Policy.
