




INSTALL IT. ENJOY QUIETNESS.

ArmaComfort AB Plus

Highly flexible acoustic comfort

- // Specially designed to reduce noise for rainwater and waste pipes
- // Thin acoustic lagging with high performance
- // Pre-cut self-adhesive sheets available
- // Easy to apply and maintain



 **armacell**[®]
ArmaComfort[™]

INSTALL IT. ENJOY QUIETNESS

ArmaComfort AB



NOISE CONTROL KEY TERMS

// **Sound** is a mechanical vibration which is perceived by the human ear in the frequency range 16 Hz to 16.000 Hz.

// **Frequency** is the number of vibrations per second. The pitch rises as frequency increases. The most important range for building acoustics lies between 100 Hz and 3150 Hz.

// **Sound Insertion loss** is the difference in sound levels measured between the bare pipe and the pipe with insulation. Such a measurement of sound reduction in dB(A) provides a direct indication of the improvement due to an acoustic solution.

// **Bel (B) and decibel (dB)** are relative units and represent the ratio between two acoustic quantities on a logarithmic scale.

// **Decibel (A), dB (A)** weights the volume according to frequencies. In this way it is possible to achieve a measurable representation of noise as it is perceived. Depending on the frequency, the human ear perceives tones of the same sound pressure as being of different loudness.



TECHNICAL DATA - ARMACOMFORT AB PLUS

Brief description	ArmaComfort AB plus combines the acoustic performance of an excellent and flexible acoustic barrier of 2 mm thickness and 4 kg/m ² of weight with a damping ArmaFlex flexible elastomeric foam of 9 mm.
Material type	Multi-layer acoustic insulation material consisting of an acoustic EPDM-EVA barrier and an elastomeric foam based on synthetic rubber.
Product colour range	Black
Special features	ArmaComfort AB Plus offers outstanding durability.
Applications	ArmaComfort AB Plus is widely used as an acoustical insulation of wastewater, rainwater and sewage pipes in residential and non-residential buildings.
Installation	Certified and compatible adhesive for a long-term performing system is ArmaFlex 520.
Declaration of performance	Declaration of Performance in accordance with Article 7(3) of Regulation (EU) No 305/2011 is available at www.armacell.com/DoP .

Property	Value / Assessment	Standard / Test method		
Temperature range				
Service temperature ^{1,2,3}	Max. °C 110	EN 14304		
Thermal conductivity				
Declared thermal conductivity	<table border="0"> <tr> <td> ϑ_m $\lambda_d \leq [W/(m \cdot K)]$ Formula </td> <td> $0 \text{ }^\circ\text{C}$ 0.042 $\lambda = [42 + 0.1 \cdot \vartheta_m + 0,0009 \cdot \vartheta_m^2]/1000$ </td> </tr> </table>	ϑ_m $\lambda_d \leq [W/(m \cdot K)]$ Formula	$0 \text{ }^\circ\text{C}$ 0.042 $\lambda = [42 + 0.1 \cdot \vartheta_m + 0,0009 \cdot \vartheta_m^2]/1000$	EN ISO 13787, EN 12667, EN ISO 8497
ϑ_m $\lambda_d \leq [W/(m \cdot K)]$ Formula	$0 \text{ }^\circ\text{C}$ 0.042 $\lambda = [42 + 0.1 \cdot \vartheta_m + 0,0009 \cdot \vartheta_m^2]/1000$			
Fire Performance and Approvals				
Reaction to fire	C-s2,d0	EN 13501-1, EN 13823, EN ISO 11925-2		
Resistance to water vapour				
Water vapour diffusion resistance factor	≥ 7,000	EN 13469, EN 12086		
Physical attributes				
Mass per unit area	11mm thickness: 3.7 - 5.0 kg/m ²			
Dimensions and tolerances	Thickness: 11 mm ± 1.6 mm Width: 1000 mm ± 1.5% Length: 2000 mm ± 1.5%	EN 822, EN 823, EN 13467		
Acoustic performance				
Weighted sound reduction index, R_w (C ; Ctr) [dB]	$R_w = 26 \text{ dB}$ (C;Ctr) = [-1;-3] dB	EN ISO 717-1, ISO 10140-1, ISO 10140-2		
System acoustic insertion loss	on plastic waste water pipes ≤ 14 dB(A) on Geberit PE HD ≤ 16 dB(A) on Geberit Silent db 20 ≤ 18 dB(A)	EN 14366		
Other technical features				
Shelf life ⁴	Self-adhesive sheets: 1 year			
Storage	Can be stored in dry and clean rooms at normal relative humidity (50% to 70%) and ambient temperature (0°C to 35°C).			

¹For use in temperatures below 0 °C, please contact our Customer Service Centre.

²For rainwater pipes with the requirement of condensation prevention, please contact our Customer Service Centre.

³Minimum service temperature: as usual in heating and plumbing systems.

⁴Shelf life (maximum storage time) is limited to ensure that only currently manufactured products are installed on projects. This limitation is restricted solely to storage of the product and does not affect the lifetime of product after it has been installed.

Roll - standard. Black

Item	Thickness [mm]	Width [m]	Length [m]	Content [metric]
AO-11-99/E-AB+	11	1	2	2 m ²

Other information

Remarks ArmaComfort AB Plus must be applied with ArmaFlex 520 and ArmaComfort Tape TAPE-PE-FE904 (IESIA00900923).
Primary content: roll in carton

Roll - standard self-adhesive. Black. Roll packed in carton

Item	Thickness [mm]	Width [m]	Length [m]	Content [metric]
AO-11-99/EA-AB+	11	1	2	2 m ²

Other information

Remarks ArmaComfort AB Plus self-adhesive must be applied with ArmaComfort Tape TAPE PE-FE904 (IESIA00900923).
Primary content: roll in carton

Sheet – self-adhesive. Black

Item	Thickness [mm]	Width [mm]	Length [m]	Outer diameter [mm]	Content [quantity]
AO-11ZSA29100	11	290	1	56	10 piece
AO-11ZSA32100	11	320	1	63	10 piece
AO-11ZSA37100	11	370	1	75	10 piece
AO-11ZSA42100	11	420	1	90	10 piece
AO-11ZSA50100	11	500	1	110	10 piece
AO-11ZSA56100	11	560	1	125	10 piece

Other information

Remarks Primary content available as 10 sheets, packed in one carton.

HT/ArmaFlex S . Tape – PVC. Black

Item	Description	Thickness [mm]	Width [mm]	Length [m]	Content [quantity]
TAPE-PE-FE904	HT/ArmaFlex S tape. Polyolefin UV-resistant carrier with adhesive on one side, self-seal.	0.23	50	25	30 roll

All data and technical information are based on results achieved under the specific conditions defined according to the testing standards referenced. Despite taking every precaution to ensure that said data and technical information are up to date, Armacell does not make any representation or warranty, express or implied, as to the accuracy, content or completeness of said data and technical information. Armacell also does not assume any liability towards any person resulting from the use of said data or technical information. Armacell reserves the right to revoke, modify or amend this document at any moment. It is the customer's responsibility to verify if the product is suitable for the intended application. The responsibility for professional and correct installation and compliance with relevant building regulations lies with the customer. This document does not constitute nor is part of a legal offer to sell or to contract.

At Armacell, your trust means everything to us, so we want to let you know your rights and make it easier for you to understand what information we collect and why we collect it. If you would like to find out about our processing of your data, please visit our Data Protection Policy.

Trademarks followed by © or ™ are trademarks of the Armacell Group. © Armacell, 2023 All rights reserved.

ArmaComfort | ArmaComfort AB Plus | Brochure | 052024 | en-GB

ABOUT ARMACELL

As the inventor of flexible foam for equipment insulation and a leading provider of engineered foams, Armacell develops innovative and safe thermal and mechanical solutions that create sustainable value for its customers. Armacell's products significantly contribute to global energy efficiency making a difference around the world every day. With more than 3,300 employees and 25 production plants in 19 countries, the company operates two main businesses, Advanced Insulation and Engineered Foams. Armacell focuses on insulation materials for technical equipment, high-performance foams for acoustic and lightweight applications, recycled PET products, next-generation aerogel technology and passive fire protection systems.

For more information, please visit:
www.armacell.com

 **armacell**[®]
ArmaComfort[™]